
LUCAS WORKSHOP INSTRUCTIONS

WINDSCREEN WIPER MODELS CW AND CR**RECOMMENDED OILS AND GREASES, ETC.****MODELS CW1, CW2 and CWX**

Duckhams Keenol KG25 grease should be used in the gearbox.

Oiline BBB, or any good grade of light machine oil, should be used to smear on the armature shaft and for soaking new porous bronze bearings before reassembly.

Duckhams HBB grease should be used for all other bearings.

MODELS CR AND CRT

Duckhams Keenol KG25 grease should be used in the gearbox.

Oiline BBB, or any good grade of light machine oil, should be used to smear on the armature shaft and for soaking new porous bronze bearings before reassembly.

Duckhams HBB grease should be used on the final gear shaft, intermediate pinion bearing, crosshead slide, crosshead pin and crankpin, cable rack, wheelbox gears and spindles.

The use of glycerine on rubber grommets

The rubber grommet or washer round the spindle of wheelboxes should be lubricated with a few drops of glycerine.

The use of methylated spirits (de-natured alcohol) on windscreens

Methylated spirits should be used to remove oil, tar spots and other stains from windscreens.

It has been found that the use of some silicone and wax-based polishes for this purpose can be detrimental to the rubber squeegees.

